

4X REAR-DISCHARGE DECKS



Committed to the Cut.®



» Scan this code for instant access to videos, user stories and information about 4XRD decks.

MIDMOUNT™ 4XRD REAR DISCHARGE™ DURAMAX® DECKS

Grasshopper DuraMax® 4X Rear Discharge™ decks are designed to advance the safety and productivity of rear discharge with the best possible cut. This dedicated rear-discharge deck offers revolutionary performance, distributing clippings evenly to avoid clumping and lowering operating costs.

Perfect for commercial contractors, municipalities, schools, cemeteries, vineyards, orchards, and mobile home and RV parks the 4XRD deck's unique four-spindle design evenly distributes clippings, eliminates windrowing, and channels material out the back and away from the operator.

The 4XRD deck allows trimming around municipal hardscaping or cemetery headstones while discharging clippings and debris away.

- Specially designed cutting chamber handles large volumes of grass and delivers a clean, level cut.
- Four-spindle design spreads load of grass clippings and debris while channeling it out the back.
- Trim with either side of the deck.
- Anvil-edged deck with 1/2-inch-thick formed steel leading edge features 7-gauge skirts and geometrically engineered design to withstand the punishments of commercial mowing.



	48-in.	52-in.	61-in.	72-in.
DuraMax® 4XRD Dedicated Rear Discharge Decks				
V Series MidMount™				
125V	•	•	•	
125VB	•			
127V, 225V-G4, 226V-G4		•	•	
M1 MidMount™				
225	•	•	•	
335B, 325D, 329		•	•	•
400D 1.3L, 440 EFI			•	•
Deck Width				
49.5 in. (125.7 cm), Width of cut 48 in. (121.9 cm)	•			
53.5 in. (135.9 cm), Width of cut 52 in. (132.1 cm)		•		
62.5 in. (158.8 cm), Width of cut 61 in. (154.9 cm)			•	
73.5 in. (186.7 cm), Width of cut 72 in. (182.9 cm)				•
Cutting Height				
1.0 to 5.0 in. (2.5 cm to 12.7 cm)	•	•	•	•
Construction (Robotically welded steel)				
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane – 25% thicker than 1/4 in. (7.95 mm) – with 7-gauge skirts for geometric strength	•	•	•	•
Spindle plane is 0.9 in. (22.86 mm) thick in stress zones; anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck	•	•	•	•
Cutting Blades (Tempered, alloy steel)				
(2) 18 in. (45.7 cm), (1) 15 in. (38.1 cm)	•			
(3) 18 in. (45.7 cm)		•		
(3) 21 in. (53.3 cm)			•	
(3) 25 in. (63.5 cm)				•
Sentry™ Spindle Assemblies				
8-inch spindle flanges, with 6-bolt pattern. 2.5 cm (approx. 1 in.) outside diameter (O.D.) shaft; double bearings; greaseable from top of deck; deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion	•	•	•	•
Machined aluminum alloy spindle housing	•	•	•	•
Blade Drive				
Belt drive with single Kevlar V-belt and idler arm tensioning	•	•	•	•

4XRD DECK OPTIONS



DURAFLEX™ SUSPENSION FORKS*

Absorb the jolts and jostles of irregular ground and maintain a level cut.



EDGE-EZE™ EDGER†

Reduce labor and time of edging up to 75%.



FLAT-PROOF FRONT TIRES

Semi-pneumatic tires will never go flat.

*Not compatible with PowerVac™ collection, or with flatproof or Tweel tires. †For M1 MidMount™ models

MOW ON AHEAD. AND THROW CLIPPINGS OUT BACK.



PowerFold® provides effortless underside deck access and allows for compact storage.




FRONTMOUNT™ 35R AND 37R SERIES REAR DISCHARGE DURAMAX® DECKS

Get the benefits of rear discharge with upfront deck reach and QuikConverter™ implement capability for government, school, fleet, cemetery, orchard, vineyard, ag or any mowing application.

The 35R and 37R Series dedicated rear-discharge decks throw grass clippings out the back of the deck while keeping clippings on the turf. Get a level, uniform cut with the ability to trim on either side of the deck saving time and minimizing cleanup of discharged clippings.

DuraMax® deck construction features Sentry™ spindles, 8-inch spindle flange with six-bolt pattern and anvil-edge design for geometric strength with 7-gauge skirts to withstand the brunt of commercial mowing.



» Standard trash shield is attached to the rear of the deck to protect the PTO shaft and coupler from discharged clippings and debris, and is hinged for terrain-following articulation and PowerFold® deck function.

	52-in.	61-in.	72-in.
DuraMax® 35R & 37R Series Dedicated Rear-Discharge Decks			
FrontMount™ Compatibility	3552	3761	3572
623KT (requires 22" tires)	•		
725KT	•	•	
725DT, 727T EFI, 729T	•	•	•
735BT	•	•	•
900D 1.3L, 932, 940 EFI		•	•
Deck Width			
53.5 in. (135.9 cm), Width of cut 52 in. (132.1 cm)	•		
62.5 in. (158.8 cm), Width of cut 61 in. (154.9 cm)		•	
73.5 in. (186.7 cm), Width of cut 72 in. (182.9 cm)			•
Cutting Height			
1.25 to 5.0 in. (3.18 cm to 12.7 cm)	•	•	•
Construction (Robotically welded steel)			
Tubular 2.25 in. x 4 in. boxed members with 0.25 in. gussets; formed, double thickness hardened steel 0.269 in. - 7.6% thicker than 0.25 in. (6.35 mm) truss spindle plane on a triple-strength upper deck, over 1/2 in. thick in stress zones; geometrically engineered design with 7-gauge skirts withstands the brunt of commercial mowing	•	•	•
Cutting Blades (Tempered, alloy steel)			
(3) 18 in. (45.7 cm)	•		
(3) 21 in. (53.3 cm)		•	
(3) 25 in. (63.5 cm)			•
Sentry™ Spindle Assemblies			
8-in. spindle flanges, with 6-bolt pattern. 2.5 cm (approx. 1 in.) outside diameter (O.D.) shaft; double bearings, greasable from top of deck; deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion	•	•	•
Machined aluminum alloy spindle housing	•	•	•
Blade Drive			
Belt drive with single Kevlar V-belt and idler arm tensioning	•	•	•
Attachment Drive			
Telescoping, splined PTO shaft		•	•
Telescoping PTO shaft	•		
Deck Wheels			
9 x 3.50 x 4 (flat-proof)	•		
11 x 4.00 x 5 (flat-proof)		•	
13 x 6.50 x 6 (rib-tread pneumatic)			•

35R & 37R SERIES DECK OPTIONS



EDGE-EZE™ EDGER

Reduce labor and time of edging up to 75%.



DECK FLOTATION INSERTS

Follow the contour of the terrain to eliminate scalping.



SPEEDTRIMMING™ ROLLER KIT

Trim with confidence against fences, buildings, walls, etc.

⚠ **WARNING:** California Proposition 65 Cancer and Reproductive Harm - www.P65Warnings.ca.gov



The Grasshopper Company • 105 Old U.S. Highway 81
P.O. Box 637 • Moundridge, KS • 67107 U.S.A.
T: **620-345-8621** • grasshoppermower.com



Litho in U.S.A. Form 0425-170903
© 2025 The Grasshopper Company
For a complete list of trademarks and registered trademarks, visit grasshoppermower.com/legal.