



Committed to the Cut.®

EDGE-EZE™ EDGER

CLEAN, SHARP EDGES IN RECORD TIME.



"We can edge from either side of the road and still face oncoming traffic to increase visibility and safety."

Scott Brewer
RCI,
Slidell, LA

Scan this code for instant access to videos, user stories and information about the Edge-EZE™ edger.



STREAMLINE THE EDGING PROCESS. REDUCE EDGING TIME UP TO 75%!

Edge-EZE™ delivers a clean, sharp edge along sidewalks, roadways and driveways, and saves valuable time and labor edging large areas and long runs.

- **Replaces two-cycle edgers** and multiple operators for increased productivity and huge cost savings.
- Dependable, heavy-duty construction makes Edge-EZE™ ideal for commercial use.
- Depth of cut is 2-1/2 inches (from hub to edge of tempered disc) for a clean, sharp edge that will satisfy the most demanding customers.
- Edge-EZE™ maintains established edge at **up to 500 ft./min.**
- Perfect for maintaining established edges. Lever raises blade for easy transport.
- Electric actuator provides additional down pressure for edging in overgrown or tough conditions. Raises blade 4 inches at the touch of a switch to cross sidewalks.
- Edge-EZE™ connects to discharge or trim side of deck easily and quickly for greater versatility.



CASE STUDY

A two-mile stretch of sidewalk at a golf course equals four miles of edging. It takes two workers with hand-held edgers 16 hours each (or 32 man-hours) of labor to maintain this each time. The same job takes one operator with a Grasshopper and Edge-EZE™ only four hours.

Annual cost of NOT using Grasshopper = \$10,228. Learn more at grasshoppermower.com/edge.

To explore our entire line of Grasshopper Commercial-Grade Implements, or find a Grasshopper dealer near you, visit grasshoppermower.com/implements.

CUTTING EDGE. EDGE-CUTTING.

grasshoppermower.com/edge



A reversible, concave, self-sharpening, tempered blade and weighted hub assembly maintain a clean, sharp edge from sidewalk, curb or turf.



Edge-EZE™ discharge shield allows you to blow debris off sidewalk into turf.



A 12-inch vertical adjustment lets you edge from street or ground level, depending on your needs.



Reverse disc by removing one bolt to edge from the turf.

Edge-EZE™ Specifications				
For DuraMax® Decks	48 in. (121.9 cm)	52 in. (132.1 cm)	61 in. (154.9 cm)	72 in. (182.9 cm)
Total width (in down position)	59.25 in. (150.5 cm)	63.25 in. (160.7 cm)	72.25 in. (183.5 cm)	83.25 in. (211.5 cm)
Total width (in up position)	60.25 in. (153 cm)	64.25 in. (163.2 cm)	73.25 in. (186 cm)	84.25 in. (214 cm)
Maximum ground clearance	12.5 in. (31.8 cm)			
Replaceable disc	Tempered steel. Order # 824149			
Disc diameter/cutting depth	11.0 in. (27.9 cm) / 2.5 in. (6.4 cm)			
Weight	85 lbs. (38.6 kg)			
Compatibility	200V-G4, 200, 300, 300G, 400, S026, 526V-52, 600, 700 & 900 Series			
Edge-EZE™ Order Numbers				
Order no.	Model			
533137	Right mount, side discharge decks			
533139	Right mount, rear discharge decks			
533142	Left mount, side/rear discharge decks			
605860	Wiring Harness (For FrontMount™ units equipped with universal wiring harness)			



Left (trim side) mount for side- and rear-discharge decks.