

POWERVAC[™] COLLECTION SYSTEM



DON'T SACRIFICE PERFORMANCE WHEN COLLECTING

Get a professional, finished cut quality **with less fatigue and less time in one pass with no overlap**. Powerful performance in all conditions allows you to handle any job, from fall leaf cleanup to debris handling and removal. More than 60 years of Grasshopper engineering and innovation continue to make PowerVac[™] the industry standard in collection technology.

6

3

"The collection unit is by far

the best I have used in 16 years


in the industry. The high-powered

suction gives you the perfect

presentational finish."

Rob Bradshaw, Head Groundsman Peterborough United Football Club Peterborough, England Grasshopper cutting decks offer superior airflow for the finest cut quality. Powerful vacuum action propels debris through the collector tube **without clogging or the need to overlap on passes**. Simply match your mowing speed to your mowing conditions for a clean sweep every time.

Find more information at: grasshoppermower.com/powervac.



Model 15B for FrontMount[™] mowers





Model 25 Fixed MountAll 700 & 900 Series



Model 15B • All 600, 700 & 900 Series

Weight is distributed across six tires for a lighter footprint requiring no counterweight.



Model 12F Triple Bag Model 12HT (inset) • All 600, 700 & 900 Series



Model 8HT Twin Bag Model 8F (not shown) • All FrontMount[™] Series

FRONTMOUNT[™] AND MIDMOUNT[™] POWERVAC[™] FEATURES.

- 1 Tapered-bottom metal hoppers compact clippings and debris, and can be emptied while the operator remains seated.
- Exclusive, easy "no-tools" Quik-D-Tatch® feature converts from collection to side discharge. See page 15.
- 3 Monitor debris as it passes through the 6-inch-diameter, reinforced semi-transparent hose.
- GrassMax[™] medium-lift blades (included with vac drive) create perfect airflow to achieve a clean, manicured cut in a wide variety of conditions.
- Sear-mounted collectors retain True ZeroTurn[™] maneuverability without cumbersome pull-behind collectors.
- 6 ClearView[™] sight windows let you monitor fill level, and can be removed for easy cleaning on Models15B, HighLift[™] 15B and 16.
- Quik-D-Tatch[®] Vac is deck-driven and quiet-running. No loud, expensive auxiliary gas motor required.
- B Dynamically balanced trash-ingesting steel impeller reduces and compacts debris with no clogging or bridging.

Slide-In Bags Meta
Model/Series 8HT, 8F 12HT, 12F
100V Series *
200V-G4 Series *
200 Series * • •
300G Series *
300 Series * • •
400 Series * • •
Collector Volume 8 cu. ft. 12 cu. ft. 1
*Counterweight required. (C) "We take pride in leaving spotless lawns by collection clippings with the PowerW Collection systems." Terry Wright Wright Way Lawn Care Cassopolis, MI

MIDMOUNT[™] POWERVAC[™]



Model 8F Twin Bag Model 8HT (not shown) • All MidMount[™] Series



Model 16M1 • All 200, 300 & 400 Series

HT MODELS FEATURE HINGED Metal Tops that prop up For easy emptying.

and the second stand and the

Model 8HT with twin, or 12HT with triple, 4-cubic-feet reinforced bags, capture clippings and debris. Bags slide in and out for easy emptying and are made of UV-tolerant, commercial-grade, rip- and tear-resistant fabric.

Check Compatibility charts to see which HT models fit FrontMount[™] and MidMount[™] mowers.



HIGHLIFT™ 158 TAKE YOUR COLLECTION SOLUTION TO A HIGHER LEVEL.

Scan this code to view a video on the HighLift™ 15B.

HighLift[™] 15B allows operators to raise and lower the collector with the flip of a switch. Infinitely variable emptying positions easily clear fences, truck beds and trailers with sidewalls and place clippings in the middle of the vehicle bed or trailer.



Watch the HighLift[™] in action and find more information at grasshoppermower.com/highlift.



"I simply drive over to the wagon, back up to it, raise the hopper above the sides of the wagon, and then open the hopper door and dump the hopper load into the wagon. I never have to leave my seat until the mowing and bagging job is complete."

> George B. Saskatchewan, Canada

HIGHLIFT" 15B - SPECIFICATIONS (FOR 700 AND 900 SERIES)

Ivedones loks	ince control for fursing/ emprying. Fuduplet required for decks equipped with rowerroud 7
Lift Height	72.0 in. (182.9 cm) measured from level surface to bottom of collector.
Lift Extension	34.0 in. (86.4 cm) measured at bottom of collector from down position to fully raised position.
Vertical Clearance	112.0 in. (284.5 cm) clearance point at top of collector in fully raised/extended position.



72 in.

🗲 34 in. 🗕

Debris Xpel[™] arms inside the hopper facilitate fast, efficient emptying. (Optional for 15B)



Raise, lower, open and close with steering lever-mounted joystick (required).



Two-part collection hose system forms a debris-free seal.



Optional dolly for the HighLift™ 15B collector makes installation and removal effortless.

OPTIONAL POWERVAC[™] ACCESSORIES

TINE-RAKE[™] DETHATCHER



Dethatchers feature a unified raking motion that removes large amounts of thatch while surface aerating the soil to promote root development. Combine with PowerVac[™] Collection System to rake and pick up thatch in one pass.

TINE-RAKE™ Specifications	46" Dethatcher (48" or 52" deck)	60" Dethatcher (61" or 72" deck)	
Total Width	46.5 in. (118.11 cm)	61.5 in. (156.21 cm)	
Order #	533460	533465	
No. of Tines (Double-loop, 2 rows offset)	35	47	
Wheel Size	8x1.75 Semi-pneumatic		
Weight	86 lbs. (39 kg)	100 lbs. (45.5 kg)	
Compatibility	526V-52, 600, 700 & 900 Series FrontMount [™] models	600, 700 & 900 Series FrontMount [™] models	
	For MidMount™ models, contact JRCO, Inc. at 800-966-844		



15B DEBRIS XPEL™ ARMS Debris Xpel™ arms inside the hopper facilitate fast, efficient emptying. Optional for fixed-mount 15B; standard equipment for HighLift[™] 15B.



15B ELECTRIC DOOR KIT Open and close fixed mount 15B from the seat at the touch of a switch. Requires joystick control or rocker switch.

REMOTE VAC[™]



The PTO-driven Remote Vac[™] quickly mounts in place of the DuraMax[®] deck. Enjoy fast, easy cleanup in hard-toreach areas where a mower cannot go. A flexible, 12-foot, 6-inch-diameter hose with a hand-held swiveling nozzle rotates 360 degrees for easy handling. Vacuum leaves and

debris and deposit them into the PowerVac™ collector.

	REMOTE VAC" SPECIFICATIONS
Weight	160 lbs. (72.6 kg)
Hose	6 in. (15.2 cm) x 12 ft. (365.8 cm) with 360-degree swiveling nozzle
Container	Any PowerVac™ metal hopper or mesh bag collection system
Compatibility	600, 700 and 900 Series FrontMount [™] models



FIXED-MOUNT 15B DOLLY Effortlessly install, remove and store fixed-mount 15B metal hoppers. Dolly steadies the

hopper while connecting bolts are installed/removed, then easily rolls away for convenient storage.

QUIK-D-TATCH[®] VAC change the way you mow without changing decks.

Exclusive, "no-tools" Quik-D-Tatch® feature converts from collection to side discharge in less than 30 seconds. Simply remove the deck-driven PowerVac[™] unit for easy conversion or to clear narrow gate openings. Note: Before engaging blades, be sure a mulching restriction plate, side discharge shield or Side Discharge Control Kit is in place.



FRONTMOUNT[™] POWERVAC[™] SPECIFICATIONS

MODEL	25	HighLift™ 15B	15B	12HT/12F	8F/8HT
Capacity					
25 cu. ft. (708 liters)	•				
15 cu. ft. (425 liters) 12 cu. ft. (340 liters)		•	•		
8 cu. ft. (227 liters)				•	•
Compatibility					
500V Series					•
600 Series			•	•	•
700/900 Series	•	•	•	•	•
Collector Type (all collectors are rear mo Metal hopper emptied by lever from driver's seat	uniea)		•		
Metal hopper, raised, lowered and emptied with					
joystick control from driver's seat		•			
Metal top with three slide-out mesh bags				• (12HT)	
Fabric top with three slide-out mesh bags				• (12F)	 (0UT)
Metal top with two slide-out mesh bags Fabric top with two slide-out mesh bags					• (8HT) • (8F)
Tail Wheels Required					- (u)
Wide-Stance Single-Fork OR Wide-Stance Double-Fork	•	•			
Wide-Stance Single-Fork OR Wide-Stance Double-Fork OR Dual-Fork (Dual-Fork not available for 900 Series with PowerVac ^{**} collector.)			•	•	•
Mount Kit					
500V Series					503559
600 Series			503540	503	-
700 Series	503583	503555	503548	503587	503586
900 Series				503	582
Quik-D-Tatch® Vac Drive Powered by a belt from the blade spindle. Mounts directly to the deck. Locked securely in place by one pin. No auxiliary engine required.	•	•	•	•	•
Hose (Two-piece hose (upper & lower) for High	Lift [™] 15B only.)				
Semi-transparent flex hose for visibility	•	•	•	•	•
and clog resistance.					
Mounted Height					46.0 in.
500V Series					(116.8 cm)
600 Series				45.0	
	61.0 in.	58.0 in.	55.75 in. (141.6 cm)	(114.	
700/900 Series	(154.9 cm)	(147.3 cm)	,	49.0 (124.	
Deck Width with Vac Unit At	tached				
42 in. deck - 54.5 in. (137.2 cm)					•
48-in. deck – 61.0 in. (154.9 cm)			•	•	•
52-in. deck – 65.0 in. (165.1 cm) 61-in. deck – 74.0 in. (188.0 cm)	•	•	•	•	•
72-in. deck – 85.0 in. (215.9 cm)	•	•	•		
Mounted Length of Power Un Deck Down (Mowing Position		and Coll	ector)		
525V (42-in) (Add 3.0 in. (7.6 cm) 526V-52-in.)					108.5 in. (275.6 cm)
600 (48- and 52-in.)			103.5 in. (262.9 cm)	104.0 in. (264.5 cm)	104.0 in. (264.5 cm)
700 (52-in.) (Add 2.0 in. (5.1 cm) for Model 725DT)	113.5 in. (288.3 cm)	115.5 in. (293.4 cm)	111.5 in. (283.2 cm)	105.5 in. (268.0 cm)	105.5 in. (268.0 cm)
700 (61-in.) (Add 2.0 in. (5.1 cm) for Model 725DT)	115.5 in. (293.4 cm)	117.0 in. (297.2 cm)	113.0 in. (287.0 cm)	108.5 in. (275.6 cm)	108.5 in. (275.6 cm)
700 (72-in.) (Add 2.0 in. (5.1 cm) for Model 725DT)	125.5 in. (318.8 cm)	126.5 in. (321.3 cm)	122.5 in. (311.2 cm)		A
900 (52-in.)	118.5 in. (301.0 cm)	120.5 in. (306.1 cm)	116.5 in. (295.9 cm)	110.5 in. (280.7 cm)	110.5 in. (280.7 cm)
900 (61-in.)	120.5 in. (306.1 cm)	122.0 in. (309.9 cm)	118.0 in. (299.7 cm)	113.5 in. (288.3 cm)	113.5 in. (288.3 cm)
900 (72-in.)	130.5 in. (331.5 cm)	131.5 in. (334.0 cm)	127.5 in. (323.9 cm)		
Weight					
Collection system only. (Does not include weight of power unit and deck)	350 lbs. (158.8 kg)	605 lbs. (274.4 kg)	285 lbs. (129.3 kg)	12HT 205 lbs. (93 kg) 12F 175 lbs. (79.4 kg)	8HT 180 lbs. (81.6 kg) 8F 160 lbs. (72.6 kg)

MIDMOUNT[®] POWERVAC[®] SPECIFICATIONS

MODEL	16	12HT, 12F	8F/8HT
Capacity			
16 cu. ft. (453 liters)	•		
12 cu. ft. (340 liters)		•	
8 cu. ft. (227 liters)			•
Compatibility			
100V Series/200V-G4 Series			•
300G4/300G5 Series		•	•
200/300/400 Series	•	•	•
Collector Type (all collectors are rear	mounted)		
Metal hopper emptied by lever from driver's seat	•		
Metal top with three slide-out mesh bags		• (12HT/M1)	
Fabric top with three slide-out mesh bags		• (12F/M1)	
Metal top with two slide-out mesh bags			• (8HT/M1)
Fabric top with two slide-out mesh bags			• (8F/M1)
Mount Kit			
100V Series/200V-G4 Series			Included w/ collector
300G4/300G5 Series			
200 Series	503551	503	550
300/400 Series	503552		
Quik-D-Tatch® Vac Drive			
Powered by a belt from the blade spindle.			
Mounts directly to the deck. Locked securely in place by one thumbscrew	•	•	•
Locked securely in place by one thumbscrew.			
Hose			
Semi-transparent flex hose for visibility and clog resistance.	•	•	•
Mounted Height			
	•		
60.5 in. (153.7 cm) 45.0 in. (114.3 cm) (Add 2 inches on 33365 & 33765)		•	
Deck Width with Vac Unit A	Machael	•	•
	machea		
41-in. deck - 52.5 in. (133.4 cm)	•		
48-in. deck — 61.0 in. (154.9 cm)			
52-in. deck - 65.0 in. (165.1 cm)			
61-in. deck — 74.0 in. (188.0 cm)			
72-in. deck — 85.0 in. (215.9 cm)	Init (Deals and		. (10) (1174))
Mounted Length of Power U			
125VB-41			99.0 (251.5 cm)
125VB-48, 125V-48, 125V-52, 127V-52			98.0 (248.9 cm)
125V-61, 127V-61			101.0 in. (256.5 cm)
225V-G4/52, 227V-G4/52 EFI			100.5 in. (255.3 cm)
225V-G4/61, 227V-G4/61 EFI			103.0 in. (261.6 cm)
226V-G4/52			99.5 in. (252.7 cm)
226V-G4/61		1070 :	102.0 in. (259.1 cm)
300G4-52		107.0 in. (271.8 cm)	106.0 in. (269.2 cm)
300G4-61/300G5-61		109.0 in. (276.9 cm)	109.0 in. (276.9 cm)
20005 72		110.0 : /007.0 .	113.0 in. (287.0 cm)
	005: 0000	113.0 in. (287.0 cm)	· · · ·
200 (48-in.)	90.5 in. (229.9 cm)	98.5 in. (250.2 cm)	98.5 in. (250.2 cm)
200 (48-in.) 200 (52-in.)	90.5 in. (229.9 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm)
200 (48-in.) 200 (52-in.) 200 (61-in.)	90.5 in. (229.9 cm) 92.0 in. (233.7 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm)
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335)	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm)
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335)	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm)
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335)	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm)
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (72-in.) (Subtract 3 inches on 3298 & 335)	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm)
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (72-in.) (Subtract 3 inches on 3298 & 335) 400 (61-in.)	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm) 107.0 in. (271.8 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm)
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (72-in.)	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm)
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (72-in.)	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm) 107.0 in. (271.8 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm)
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (72-in.) (Subtract 3 inches on 3298 & 335) 400 (61-in.) 400 (72-in.) Weight 100V Series/200V-G4 Series	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm) 107.0 in. (271.8 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm) ▲
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 400 (61-in.) 400 (72-in.) Weight 100V Series/200V-64 Series Collection system only; includes required	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm) 107.0 in. (271.8 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm) ▲ 8HT 230 lbs. (104.3 kg)
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (72-in.) Weight 100V Series/200V-64 Series Collection system only; includes required counterweight	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm) 107.0 in. (271.8 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm) ▲ 8HT 230 lbs. (104.3 kg) 8F
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 400 (61-in.) 400 (72-in.) Weight 100V Series/200V-G4 Series Collection system only; includes required counterweight (Does not include weight of power unit and deck)	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm) 107.0 in. (271.8 cm) 110.5 in. (280.7 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm) ▲ 8HT 230 lbs. (104.3 kg) 8F 220 lbs. (99.8 kg)
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (72-in.) (Subtract 3 inches on 3298 & 335) 400 (61-in.) 400 (72-in.) Weight 100V Series/200V-G4 Series Collection system only; includes required counterweight (Does not include weight of power unit and deck) 300G4/300G5 Series	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm) 107.0 in. (271.8 cm) 110.5 in. (280.7 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm) & 8HT 230 lbs. (104.3 kg) 8F 220 lbs. (99.8 kg) 8HT
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (72-in.) (Subtract 3 inches on 3298 & 335) 400 (61-in.) 400 (72-in.) Weight 100V Series/200V-G4 Series Collection system only; includes required counterweight (Does not include weight of power unit and deck) 300G4/300G5 Series Collection system only; includes required	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 105.5 in. (275.6 cm) 107.0 in. (271.8 cm) 110.5 in. (280.7 cm) 110.5 in. (280.7 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm) ▲ 8HT 230 lbs. (104.3 kg) 8F 220 lbs. (99.8 kg) 8HT 230.0 lbs. (104.3 kg)
30065-72 200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (72-in.) (Subtract 3 inches on 3298 & 335) 400 (72-in.) Weight 100V Series/200V-G4 Series Collection system only; includes required counterweight (Dees not include weight of power unit and deck) 300G4/300G5 Series Collection system only; includes required counterweight (Dees not include weight of power unit and deck)	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm) 107.0 in. (271.8 cm) 110.5 in. (280.7 cm) 110.5 in. (280.7 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm) ▲ 8HT 230 lbs. (104.3 kg) 8F 230.0 lbs. (104.3 kg) 8F
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (51-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (72-in.) (Subtract 3 inches on 3298 & 335) 400 (61-in.) 400 (72-in.) Weight 100V Series/200V-G4 Series Collection system only; includes required counterweight (Does not include weight of power unit and deck) 300G4/300G5 Series Collection system only; includes required counterweight	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm) 107.0 in. (271.8 cm) 110.5 in. (280.7 cm) 110.5 in. (280.7 cm) 12HT 315.0 lbs. (142.9 kg) 12F 280.0 lbs. (127.0 kg)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm) ▲ 8HT 230 lbs. (104.3 kg) 8F 220 lbs. (99.8 kg) 8F 220.0 lbs. (99.8 kg)
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (51-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (72-in.) (Subtract 3 inches on 3298 & 335) 400 (61-in.) 400 (72-in.) Weight 100V Series/200V-G4 Series Collection system only; includes required counterweight (Does not include weight of power unit and deck) 300G4/300G5 Series Collection system only; includes required counterweight (Does not include weight of power unit and deck) 200/300/400 Series	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm) 107.0 in. (271.8 cm) 110.5 in. (280.7 cm) 110.5 in. (280.7 cm) 110.5 in. (280.7 cm) 121 121 121 121 121 121 121 121 121 12	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm) ▲ 8HT 230 lbs. (104.3 kg) 8HT 230.0 lbs. (104.3 kg) 8F 220.0 lbs. (104.3 kg) 8F 220.0 lbs. (104.3 kg) 8F 220.0 lbs. (104.8 kg) 8HT
200 (48-in.) 200 (52-in.) 200 (61-in.) 300 (48-in.) (Subtract 3 inches on 3298 & 335) 300 (52-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) (Subtract 3 inches on 3298 & 335) 300 (61-in.) 400 (72-in.) Weight 100V Series/200V-G4 Series Collection system only; includes required counterweight (Does not include weight of power unit and deck) 300G4/300G5 Series Collection system only; includes required counterweight	90.5 in. (229.9 cm) 92.0 in. (233.7 cm) 95.5 in. (242.6 cm) 95.5 in. (242.6 cm) 98.0 in. (248.9 cm) 101.5 in. (250.2 cm) 100.0 in. (254.0 cm) 103.5 in. (262.7 cm)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 105.0 in. (266.7 cm) 108.5 in. (275.6 cm) 107.0 in. (271.8 cm) 110.5 in. (280.7 cm) 110.5 in. (280.7 cm) 12HT 315.0 lbs. (142.9 kg) 12F 280.0 lbs. (127.0 kg)	98.5 in. (250.2 cm) 98.5 in. (250.2 cm) 100.0 in. (254.0 cm) 102.5 in. (260.4 cm) 102.5 in. (260.4 cm) 104.0 in. (264.2 cm) ▲ 107.0 in. (271.8 cm) ▲ 8HT 230 lbs. (104.3 kg) 8F 220 lbs. (99.8 kg) 8F 220.0 lbs. (99.8 kg)

NOTE: Optional Michelin® X® Tweel® drive and caster tires are not for use with PowerVac™ collection systems.

• Standard 🔺 Not Recommended





