

300 SERIES AIR-COOLED MIDMOUNT™

Unexpected power in the straightaways

LIMITED WARRANTY†

3 YEAR

—UNLIMITED—
COMMERCIAL

LIMITED WARRANTY†

4 YEAR

800 HRS
RESIDENTIAL

ComfortReach™ with “no tools”
2-in. adjustment range



3358
BIG BLOCK™

52

61

72

993 cc, V-twin OHV
Vanguard BIG BLOCK™
air-cooled horizontal
crankshaft gasoline
engine

A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

DURABILITY & LONGEVITY

Power, efficiency and economy-equipped with a heavy-duty, Vanguard Big Block engine, with horizontal crankshaft for longer performance life, giving you intense mowing power in a surprisingly compact design.

Robust, design-matched G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7 micron absolute filter partnered with wheel motors create a fully hydraulic system for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

MANICURED CUT

5.5-inch deep DuraMax® decks with anvil-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

COMFORT & ERGONOMICS

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar and coil-spring suspension provides all-day comfort. The adjustable cup holder makes it convenient to tote along your favorite beverage. Electronic fuel gauge/hour meter on the console is standard.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit. No tools required.

The 12.0 gal/45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing to provide the quality cut you expect.

Mowing speeds up to 10.5
MPH and 6.88 acres/hr. based
on 72" cutting width*
For more details visit:
grasshoppermower.com/acres



► DuraMax® deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck
- » Speed-Trimming™ heavy-duty roller (61" and 72")
- » TrimAide™ Roller (52")
- » Electric height adjustment
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks
- » LED work lights
- » QuikAjust Tilt™ steering levers with “no tools” 9-inch comfort range
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Front Casters
- » Edge-EZE™ edger
- » Shielded sprayer
- » Aluminum or Vinyl Sunshade Canopy
- » Yellow beacon light
- » Filter minder
- » Side discharge control kit
- » Air Dam kit – for dry, dusty conditions
- » String trimmer mount kit

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements. Models may be shown with optional equipment. *Actual results may vary. † See warranty card for details

AIR-COOLED 300 SERIES-SPECIFICATIONS

MODEL – CUTTING WIDTH	● Standard ○ Option	335B 52"	335B 61"	335B 72"
ENGINE				
Type/Displacement/Cylinders				
B&S Vanguard Big Block / 60.6 cu. in. (993 cc) / V-twin	●	●	●	●
Crankshaft / Cooling System				
Horizontal / Air	●	●	●	●
Fuel / Capacity				
Gasoline - unleaded / 12 U.S. Gal. (45.4 l)	●	●	●	●
Air Cleaner				
Heavy-duty, remote-mounted engine air cleaner with replaceable element	●	●	●	●
DECKS – Side Discharge or Dedicated 4X Rear Discharge (4XRD)				
Construction (Robotic-welded steel) – Side discharge or optional 4X Rear Discharge				
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick - more than 25% thicker than 0.25 in. (6.35 mm) - with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.	●	●	●	●
Blades (MARBAIN®, 1/4-in.)				
(3) 18 in. (45.7 cm) - high-lift blades standard	●			
(3) 21 in. (53.3 cm) - high-lift blades standard		●		
(3) 25 in. (63.5 cm) - high-lift blades standard				●
Sentry™ Spindle Assemblies				
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.	●	●	●	●
Spindle Housing – 8-in. (20.3 cm)-diameter with 6-bolt pattern				
Machined aluminum	●	●	●	●
QuikAjust™ DropPin™ Height Adjustment				
Foot-controlled height adjustment pedal with pin	●	●	●	●
Cutting Height Range				
1.0 – 5.0 in. (2.5 – 12.7 cm)	●	●	●	●
Blade Drive				
Belt drive with single Kevlar® V-belt and idler arm tensioning	●	●	●	●
DEDICATED 4X REAR DISCHARGE DECK OPTION - Additional Information				
4th Spindle and Grass Thrower Blade				
Cast iron thrower spindle housing - 5-in. (12.7 cm) -diameter with 4-bolt pattern	●	●	●	●
(1) 18 in. Grass Thrower Blade	●			
(1) 18 in. High-Low Mulching Grass Thrower Blade		●	●	●
STARTER & ELECTRICAL SYSTEM				
Maintenance-Free Battery/Charging Capacity/Starter				
12 volt/20 amp/solenoid shift	●	●	●	●
Ignition				
Breakerless	●	●	●	●
Interlock System				
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	●	●	●	●
ULTIMATE OPERATOR STATION™				
Premium Comfort Seat				
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	●	●	●	●
Premier Suspension Seat	○	○	○	○
Operator Protection				
ROPS with seat belt	●	●	●	●

MODEL – CUTTING WIDTH	● Standard ○ Option	335B 52"	335B 61"	335B 72"
Suspension				
InFrame® suspension with iso-mounted seat and footrest	●	●	●	●
Console-Mounted Instruments				
Low engine oil pressure and parking brake warning lights, combination electronic fuel gauge/hour meter, ignition and push/pull PTO switches. Choke integrated with throttle lever.	●	●	●	●
Work Lights (Pre-wired)				
LED	○	○	○	○
TRANSMISSION & STEERING				
Type				
Design-matched G² hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 16 cc piston-type pumps and high-torque Parker wheel motors.	●	●	●	●
Filtration/Hydro Fluid				
7 micron absolute, spin-on / Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals.	●	●	●	●
Speed				
0 – 10.0 mph (0 – 16.1 kph) forward	●			
0 – 10.5 mph (0 – 16.9 kph) forward		●	●	●
0 – 6.0 mph (0 – 9.7 kph) reverse	●	●	●	●
Turning Radius				
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.	●	●	●	●
Steering				
One- or two-handed operation with ComfortReach™ adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.	●	●	●	●
Brakes				
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	●	●	●	●
Disc brakes	●	●	●	●
Clutch				
Heavy-duty electric MagStop blade clutch/brake	●	●	●	●
POWER UNIT TIRE SIZES				
Drive Wheels (4-ply rated): 23 x 10.5-12 turf	●			
Drive Wheels (4-ply rated): 24 x 12-12 turf	○	●	●	●
Drive Wheels (4-ply rated): 24 x 12-12 bar tread	○	○	○	○
Front Casters: 13 x 6.5-6; rib tread, pneumatic with greasable, double-sealed bearings to protect from grass wrap	●	●	●	●
POWER UNIT DIMENSIONS WITH DURAMAX® DECKS				
Mulch or 4XRD Width*/Length: 53.5 in. (135.9 cm) / 79.5 in. (201.9 cm)	●			
Mulch or 4XRD Width*/Length: 62.5 in. (158.8 cm) / 81.0 in. (205.7 cm)		●		
Mulch or 4XRD Width*/Length: 73.5 in. (186.7 cm) / 84.5 in. (214.6 cm)				●
*Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector down.				
Height (seat back/seat cushion) 49.5 in. (125.7 cm)/31.5 in. (80.0 cm)	●			
Height (seat back/seat cushion) 50.0 in. (127.0 cm)/32.0 in. (81.3 cm)		●	●	●
Height (ROPS): 70.0 in. (177.8 cm)	●	●	●	●
WEIGHT				
Uncrated**: 1140 lbs. (517.1 kg)	●			
Uncrated**: 1190 lbs. (539.8 kg)		●		
Uncrated**: 1280 lbs. (580.6 kg)			●	●
**Mulching package kit weights with high-low mulching blades: 52-in. – 29 lbs. (13.2 kg); 61-in. – 36 lbs. (16.3 kg); 72-in. – 44 lbs. (20.0 kg)				