

200V-G4 SERIES AIR-COOLED MIDMOUNT™

Take performance
to the next level.



LIMITED WARRANTY†

2 YEAR
— 800 HRS —
COMMERCIAL

LIMITED WARRANTY†

4 YEAR
— 800 HRS —
RESIDENTIAL

225V-G4

52

61

747cc, V-twin, OHV
Kohler Confidant
gasoline engine

226V-G4

52

61

810cc, V-twin, OHV
Vanguard
gasoline engine

Mowing speeds up to 9 MPH and
5.00 acres/hr. based on 61" cutting width*

For more details visit:
grasshoppermower.com/acres



● Standard deck

Enjoy comfort, performance and durability with a compact 200V Series mower. An ergonomic design and integrated, multi-point suspension, coupled with the industry's most comfortable seat, lets you stay comfortably in control — even at faster mowing speeds. A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

DURABILITY & LONGEVITY

Choose from two vertical-shaft engines. The Model 225V-G4 is powered by a 747 cc Kohler V-twin engine. Or, pick the 810 cc Vanguard 226V-G4. Both models feature G4 Hydro-Gear ZT-4400 transmissions, which are self-contained, heavy-duty commercial transaxles that provide powerful, smooth response. Integrated cooling fans and 1-3/8-inch axles extend service life, and best-in-class transmission fluid change intervals reduce costs and maintenance time. Grasshopper's intelligent design transfers more power to the cutting deck to maintain optimum blade tip speed and enhance cut quality.

Only two Access-Eze™ lubrication points cut maintenance time up to 95%.

MANICURED CUT

5.5-inch-deep decks designed for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAdjust™ DropPin™ Height Adjustment makes cutting height change fast and simple. Optional four-spindle 4XRD dedicated rear-discharge decks evenly distribute clippings under the mower and out back for a smooth cut and no windrowing.

COMFORT & ERGONOMICS

The deep-cushioned, deluxe Premium Comfort seat features a coil-spring suspension and padded lumbar support with sliding 2-inch fore and aft adjustment for all-day comfort. Iso-mounting eliminates vibration even before it reaches the seat, and both padded seat and foldable armrests are covered in scuff-resistant, breathable CoolTemp Cordura® fabric, which dissipates heat and won't tear or crack with extended use.

QuikAdjust Tilt™ steering levers with "no tools" adjustment provide a 9-inch range for maximum comfort and fit.

The 6.5 gal/24.6L single-fill fuel tank under the seat lowers the center of gravity of the machine, providing traction and stability for an enhanced ride. Standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems
- » Down Discharge™ mulching packages
- » 4X Rear Discharge™ decks
- » Side discharge control kit
- » Foot pedal extension kit for QuikAdjust™ DropPin™ height adjustment
- » TrimAide™ anti-scalp roller kit – for 52-inch decks
- » Speed-Trimming™ heavy-duty anti-scalp roller kit – for 61-inch decks
- » Air Dam kit – for dry, dusty conditions
- » LED work lights – plug-in ready
- » Yellow beacon light
- » Sunshade Canopy – vinyl or aluminum
- » Custom Cordura® weather cover
- » GrassMax™ blade options
- » Heavy-duty, grass-grooming striping kit
- » Wide seat conversion kit
- » Extended levers for taller operators
- » Foldable ROPS with adjustable seat belt

- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels
- » Edge-EZE™ edger
- » String Trimmer Mount Kit
- » DuraFlex™ suspension forks



Optional DuraFlex™
Suspension Fork

AIR-COOLED 200V-G4 SERIES-SPECIFICATIONS

MODEL – CUTTING WIDTH	● Standard ○ Option	← KOHLER →		← VANGUARD →	
		225V-G4	225V-G4	226V-G4	226V-G4
		52	61	52	61
ENGINE					
Type/Displacement/Cylinders					
Kohler Confidant gasoline/45.6 cu. in. (747 cc)/V-twin	●	●			
Vanguard – gasoline/49.4 cu. in. (810 cc)/v-twin				●	●
Lubrication System					
Pressure Lube, Filter					
Crankshaft / Cooling System					
Vertical / Air					
Fuel / Capacity					
Gasoline - unleaded / 6.5 U.S. Gal (24.6 L)	●	●		●	●
Air Cleaner					
Heavy-duty cyclonic air filter with QuadClean™ multi-stage air filtration	●	●			
Remote-mounted, centrifugal multi-stage air cleaner with advanced debris management				●	●
Muffler					
Ultra-quiet, single, industrial type					
DECKS – Side Discharge or Dedicated 4X Rear Discharge (4XRD)					
Construction (Robotic-welded steel)					
Double-layered 10-gauge plus 10-gauge formed-steel spindle plane 0.269 in. (6.83 mm) thick with 7-gauge skirts					
Spindle plane is 0.9 in. (22.86 mm) thick in stress zones; anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck (See Page 8 for thickness diagram)					
Blades (MARBAIN®, 1/4-in.)					
(3) 18 in. (45.7 cm)	●			●	
(3) 21 in. (53.3 cm)			●		●
Spindle Assemblies					
Turned, ground and polished 2.5 cm (approx. 1 in.) outside diameter (O.D.) precision shaft; spindle head designed to eliminate fiber wrap; double bearings, non-greasable					
Spindle Housing					
8-in. (20.3 cm)-diameter machined aluminum housing with 6-bolt pattern					
Spindle Cones					
Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion					
QuikAdjust™ DropPin™ Height Adjustment					
Foot-controlled height adjustment pedal with pin					
Cutting Height Range					
1.0 – 4.5 in. (2.5 – 11.4 cm) in 1/4-inch increments					
Blade Drive					
Belt drive with single Kevlar V-belt & idler arm tensioning					
DEDICATED 4X REAR DISCHARGE DECK OPTION - Additional Information					
4th Spindle and Grass Thrower Blade					
Cast iron thrower spindle housing – 5-in. (12.7 cm) -diameter with 4-bolt pattern	●	●		●	●
(1) Grass Thrower Blade	●			●	
(1) 18 in. High-Low Mulching Grass Thrower Blade		●			●
STARTER & ELECTRICAL SYSTEM					
Maintenance-Free Battery/Charging Capacity/Starter					
12 Volt/15 amp/solenoid shift	●	●			
12 Volt/16 amp/solenoid shift				●	●
Ignition					
Breakerless					
Interlock System					
Prevents engine start when PTO clutch is engaged or steering levers are in drive position; allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral					
ULTIMATE OPERATOR STATION™					
Premium Comfort Seat					
Iso-mounted, high-back, deep-cushioned, foam-padded Cordura®-covered, padded foldable arms, padded backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back; adjustable fore and aft					
Operator Protection					
Rollover Protection Structure (ROPS) with seat belt					
Suspension					
Roomy, iso-mounted footrest with Shock Impact Reduction System™ (SIRS™)					

MODEL – CUTTING WIDTH	225V-G4	225V-G4	226V-G4	226V-G4
	52	61	52	61
Console-Mounted Instruments				
Low engine oil pressure, digital hour meter, parking brake indicator light, ignition switch and push/pull PTO switch. Choke integrated with throttle lever.				
Work Lights (Pre-wired)				
LED (optional)				
TRANSMISSION & STEERING				
Type				
Heavy-duty Hydro-Gear ZT-4400 hydrostatic transmissions with cooling fans; integrated transaxles with 12 cc piston pumps and 16 cc piston motors, gear reduction, internal disc brakes, and 1-3/8 inch axles				
Filtration/Hydro Fluid				
Self-contained fluid and internal filtration / CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for extended service intervals after 100-hour break in oil change				
Speed				
0 – 9.0 mph (0 – 14.5 kph) forward				
0 – 6.0 mph (0 – 9.7 kph) reverse				
Turning Radius				
True zero degree, turns within own length with counter-rotating, independently powered drive wheels				
Steering				
One- or two-handed operation with QuikAdjust Tilt™ dual levers with 9-inch comfort range that automatically return to neutral from either forward or reverse position				
Brakes				
Dynamic braking through hydrostatic transmission				
Parking Brake				
Internal disc brake in transmission				
TIRE SIZES				
Drive Wheels – Standard (5-bolt pattern)				
23 x 10.5-12 turf type, 4-ply rated				
24 x 12-12 turf type, 4-ply rated				
24 x 12-12 bar tread, 4-ply rated				
24 x 12-12 Airless Turf Tweel Drive Wheel				
Front Casters				
13 x 6.5-6 rib tread, pneumatic with double-sealed bearings				
DIMENSIONS (Mower & Deck)				
Mulch Width/Length (Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector.) Mulching kit optional.				
53.5 in. (135.9 cm)/76.0 in. (193.0 cm)				
62.5 in. (158.8 cm)/79.0 in. (200.7 cm)				
Height (Seat back)				
46.0 in. (116.8 cm)				
Height (Seat cushion)				
30.0 in. (76.2 cm)				
Height (ROPS)				
68.0 in. (172.7 cm)				
Drive Tire Track Width (outside edge to outside edge)				
50.0 in. (127.0 cm)				
WEIGHT				
Uncrated: (Mower & Deck) 960 lbs. (435.4 kg)				
Uncrated: (Mower & Deck) 980 lbs. (444.5 kg)				
Uncrated: (Mower & Deck) 1030 lbs. (467.2 kg)				
Uncrated: (Mower & Deck) 1050 lbs. (476.3 kg)				
Mulching Package (Package includes high-low mulching blades.)				
29 lbs. (13.2 kg)				
36 lbs. (16.3 kg)				